



A NAVISTAR COMPANY

INTERNATIONAL® Engines for High Performance Trucks 4000, 7000, and 8000 Series and IC Corporation School Buses

Model	12 Code Fed/Cal	Rated		Peak		Governed RPM	High Idle RPM	Clutch Torque @ 800 RPM
		HP	RPM	Torque	RPM			
VT 275	NRN	200	2700	440	1800	3000	3600	210
VT 365	NRP	175	2600	460	1400	2800	2950	340
	NRR	200	2600	520	1400	2800	2950	340
	NRS	215	2600	540	1400	2800	2950	340
	NRT	230	2600	620	1500	2800	2950	340
DT 466	NPL	210	2300	520	1400	2600	2770	400
	NPM	220	2200	540	1400	2600	2770	400
	NPN	225	2300	560	1400	2600	2770	400
	NPP	245	2300	620	1400	2600	2770	400
	NPT	255	2300	660	1400	2600	2770	400
	(High Torque) NPR	225	2300	620	1400	2400	2600	420
	(High Torque) NPS	245	2300	660	1400	2400	2600	420
	(High Torque) NPU	260	2300	800	1400	2400	2600	420
	(High Torque) NPV	285	2300	800	1400	2400	2600	420
	(High Torque) NPX	300	2300	860	1400	2400	2600	420
DT 570	NPW	285	2000	800	1200	2200	2425	700
	NPZ	310	2000	950	1200	2200	2425	700
	NRB	330	2000	950	1200	2200	2425	700
HT 570	NRA*	300	2000	950	1000	2200	2425	700
	NRC, NRD**	295	2000	950	1200	2100, 2200	2325, 2425	700
	NRE, NRG**	310	2000	1050	1200	2100, 2200	2325, 2425	700
	NRH	330	2000	1150	1200	2100	2325	700
	NRZ	340	2000	1150	1200	2100	2325	700

VT 365 Engines—Change engine oil and filter at 10,000 miles (16,000km)/350hrs/1,500 gallons of fuel

DT 466/570 and HT 570 Engines—Change engine oil and filter at 15,000 miles (24,000km)/550 hrs/2,100 gallons of fuel

All 2004 International engines are equipped with Electronically Controlled Turbochargers (EVRT™)

*NRA = Off highway only

**2 Governed speeds represent automatic and manual transmission (2100 RPM for manual; 2200 RPM for automatic)

2007 HORSE POWER & TORQUE RATINGS

Model	12 Code	Rated		Peak		Governed RPM	High Idle RPM	Clutch Torque @ 800 RPM
		HP	RPM	Torque	RPM			
MaxxForce 5	NTM	200	2700	440	1800	3000	3600	210
MaxxForce 7	NTE	200	2600	560	1400	2800	2950	350
	NTG	215	2600	560	1400	2800	2950	350
	NTH	230	2600	620	1400	2800	2950	350
MaxxForce DT	NSK	210	2300	560	1400	2600	2700-A / 2775-M	400
	NSM	225	2300	560	1400	2600	2700-A / 2775-M	400
	NSL	225	2300	620	1400	2600	2700-A / 2775-M	400
	NSG	245	2300	620	1400	2600	2700-A / 2775-M	400
	NSZ	255	2300	660	1400	2600	2700-A / 2775-M	400
	NSV	230	2300	620	1400	2400	2600	420
	NTA	260	2300	800	1400	2400	2600	420
	NTB	285	2300	800	1400	2400	2600	420
	NSH	300	2300	860	1400	2400	2600	420
MaxxForce 9	NTC	300	2000	800	1200	2200	2425	700
	NSJ	310	2000	950	1200	2200	2425	700
	NSX	330	2000	950	1200	2200	2425	700
MaxxForce 10	NST / U	310	2000	1050	1200	2100-M / 2200-A	2325-M / 2425-A	700
	NSP / W	330	2000	1150	1200	2100-M / 2200-A	2325-M / 2425-A	700
	NSN / Y	350	2000	1150	1200	2100-M / 2200-A	2325-M / 2425-A	700
MaxxForce 11	BAA	330	1800	1250	1000	2200		660
	BAB	370	1800	1350	1000	2200		760
	BAC	390	1800	1450	1000	2200		830
MaxxForce 13	BAJ	410	1800	1450	1000	2200		830
	BAK	430	1800	1550	1000	2200		830
	BAL	475	1800	1700	1000	2200		960

Key A = Automatic Transmission
M = Manual Transmission or Automated Manual Transmission

